

- sepia brown
- creme white
- grey white
- beige
- maize yellow
- brown beige
- saffron yellow
- grey beige
- vermillion
- pure orange
- flame red
- ruby red
- purple red
- red violet
- blue lilac
- ultramarine blue
- light blue
- cobalt blue
- pigeon blue
- turquoise green
- pastel green
- traffic green
- light green
- iron grey
- stone grey
- clay brown
- red brown
- deep black
- pure white
- light grey
- heather violet
- sand yellow
- daffodil yellow
- pastel orange
- azure blue
- anthracite grey
- black grey
- blue grey
- pebble grey
- white aluminium
- grey aluminium
- traffic white
- traffic black
- nut brown
- chocolate brown
- oyster white
- capri blue
- olive green
- window grey
- dusty grey
- silk grey
- light ivory
- traffic yellow
- broom yellow
- wine red
- oxide red
- telemagenta
- sapphire blue
- emerald green
- reseda green
- may green
- squirrel grey
- basalt grey
- slate grey
- concrete grey
- graphite grey
- traffic grey A
- telegrey 4
- ochre brown
- copper brown
- black brown
- signal white

- graphite black
- papyrus white
- signal yellow
- yellow orange
- carmine red
- signal blue
- pine green
- telegrey 2
- traffic orange
- black red
- turquoise blue
- mint green
- traffic grey B
- steel blue
- rosa
- pastel blue

Smell: Characteristic

Degree of gloss:

- semi mat, 25 ±5
- gloss, >75
- mat, 10 ±2

Efficiency: 400 ML – 0.8 - 1.5 m²

Dust dry: 10 min

Dry to touch: 30 min

Completely dry: 2 h

Overcoatable: 24 h

Surfaces: wood, metal, paper, glass or paintable hard plastics as well as for many textiles

Minimum Working Temperature: 10 °C

Maximum Working Temperature: 25 °C

Flash point: n.a.

Storage stability: 10 years

Content: 400 ML

How to use

The surface has to be clean, dry and free from fat.

Remove residues of old paintings and rust, then sand and prime if necessary. Let dry for 1 - 2 hours.

Use Pastic Primer on plastic parts.

Cover areas not to be painted.

Before use, shake the can for 3 minutes.

Test spray at an invisible spot to check colour-matching and compatibility of the lacquer.

Spray from a distance of approx. 25 cm several thin coats.

Do not spray over synthetic paints.

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of August 4, 2025 – This release replaces all eventually earlier issued versions.