

DUPLI-COLOR CAR'S METALLIC

Technical Information



Quick-drying acrylic lacquers for styling, contrast lacquering and repairs on the vehicle.

Ord.-no: 706837, 706844, 706851, 706868, 706875

Quality & properties

- High-grade nitrocombi quality
- Very good coverage
- Excellent adhesion
- Good flow, smooth surface
- Durable gloss
- Quick-drying
- Suitable for indoors and outdoors applications
- Weather-resistant, light-proof, UV-resistant (non-yellowing)
- Can be polished and is dirt-repellent after coating with 2-coat clear lacquer
- Scratch-, shock- and impact-resistant
- High surface hardness and good elasticity

Physical & chemical data

- Base: Nitrocombi resin
- Colourname:
 - azure blue
 - blue
 - pastel green
 - red
 - black
- Smell: Characteristic
- Degree of gloss: high gloss, >85
- Efficiency: 400 ML – 1.3 m²
- Dust dry: 10 min
- Dry to touch: 50 min
- Completely dry: 24 h
- Overcoatable: 30 min
- Surfaces: indoors and outdoors applications
- Minimum Working Temperature: 10 °C
- Maximum Working Temperature: 25 °C
- Flash point: n.a.
- Storage stability: 10 years
- Content: 400 ML

How to use

Derust surface, then clean from dirt and fat.
Egalize uneven surfaces (apply putty, sand down).
If application of putty is not necessary, apply a primer. Otherwise apply a filler to the fine-sanded area.
Before mask off the repair spot generously.
In case you work on bigger surfaces, we recommend to mask off seams and edges of the bodywork.
The ground has to be clean, dry and free from fat.
Mask off areas you do not want to paint.
Test spray.
Before use, shake the can for approx. 3 minutes.
The spray distance should be approx. 20 - 30 cm.
Apply the cover coat in several thin layers in 3 - 5 minute intervals.
Do not spray over synthetic paints!

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of August 4, 2025 – This release replaces all eventually earlier issued versions.