

MOTIP Sealing Spray

Technical Information



MOTIP Sealing Spray is an easy to use flexible coating to seal and fill small leaks and cracks. It maintains its flexibility even with temperature changes and is suitable to use on different substrates, such as, metal, plastic, PVC, concrete, and vinyl. Sealing Spray can be used indoor and outdoor and is therefore ideal to seal small leaks and cracks on gutters, ventilations, drains and similar. MOTIP Sealing Spray is weatherproof, UV-resistant and over-paintable with different paint systems.

Ord.-no: 07307, 07308, 07309

Quality & properties

- Waterproof
- Flexible
- High filling properties
- Weather- and UV-resistant
- Over-paintable with different paint systems
- User-friendly
- For indoor and outdoor use

Physical & chemical data

- Base: Synthetic resin
- Colourname:
 - black
 - grey
 - white
- Smell: Characteristic
- Degree of gloss: mat, 10 ±2
- Dust dry: 10 - 20 min
- Dry to touch: 20 - 30 min
- Overcoatable: 24 h
- Surfaces: Metal, plastic, PVC, concrete, vinyl
- Minimum Working Temperature: 10 °C
- Maximum Working Temperature: 25 °C
- Flash point: n.a.
- Storage stability: 10 years
- Content: 500 ML

How to use

Before use, carefully read the directions on the packaging and act accordingly.

The surface should be clean, dry and free of grease. Remove loose old lacquer and rust and lightly sand the surface. Clean and dry the surface again.

The aerosol should have room temperature. Best processing temperature 10 to 25°C.

Before use, shake the aerosol for 2 minutes and spray a sample. Distance to the surface to be treated approximately 25 to 30 centimeter.

Apply a first layer and let it dry for approximately 20 to 25 minutes.

Then apply a second layer, allow to dry for 5 minutes and check if the surface is sealed. If not, apply another layer.

Before applying the next layer, again shake the aerosol. Allow a drying time of 5 minutes between the different layers.

After use, clean the valve (turn aerosol upside down and press the nozzle for approximately 5 seconds).

The drying time depends on the ambient temperature, the humidity of the air and the thickness of the layer applied.

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of August 4, 2025 – This release replaces all eventually earlier issued versions.