

## EASY WASH

### Stain/ Scuff Resistant Paint Matte Finish

### CS 415

All Acrylic premium quality stain and scuff resistant coating, based on its innovative microscopic ceramic beads technology. Highly durable to household stains preventing them from soaking into the film. It creates a protective surface with the highest resistance to stains such as, tea, juice, coffee, soft drinks, ketchup, mustard, mud, chocolate and non-permanent markers. Innovative scuff-resistant formula, it will hold up to repeated cleaning without causing damage to the paint, keeping walls looking freshly painted. Easy to clean, ideal for use on children rooms schools, nurseries, hotels, locker rooms, hospitals and other commercial spaces. Produces a beautiful matte finish with excellent hiding, fast dry and it is spatter free. Odorless, formulated without ammonia, provides a mildew resistant coating.



**CLEANING:** Full properties are achieved after two weeks completing the painting. Stains and scuff marks can be removed with a wet sponge, water and mild clear soap.


#### Performance Features

- Easy to clean, resist staining based on its microscopic ceramic beads technology
- Innovative scuff-resistant formula, it will hold up to repeated cleaning without causing damage to the paint, keeping walls looking freshly painted.
- Dries to an attractive matte finish.
- Spatter-resistant, excellent opacity.
- Contains mildew side to control fungi.
- It is odorless, without ammonia
- Dries quickly

**Colors :** White and over 3.500 tinted colors are available.

**Toxicity:** Formulated without lead or mercury

**Gloss Level:** 0-5 at 60 degree viewing angle.



#### Performance Guide:

##### Weather Resistance

No recommended for exterior use.

##### Heat Resistance

60° C.

##### Water Resistance

Washable. Allow two weeks after application for firm to cure.

##### Abrasion Resistance

excellent abrasion resistance

##### Solvent Resistance

Good resistance to white spirits. Sensitive to aromatic hydrocarbons and alcohols.



**VOC (Volatile Organic Compounds):** EU Limit value for this product category A/a type WB: Interior matt walls and ceilings (gloss <25@60°), 30g/l (2010). This product contains max 5g/l VOC

Spreading Rate	Volume Solids	Wet Film Thickness	Dry Film Thickness
12 - 14 m <sup>2</sup> /L	33%	97 micrometres	33 micrometres
Dry Time at 20°C	Flexibility	Thinning	For Application By
1 hour to touch 2-4 hours to recoat	Passes 6mm mandrel	5% water if necessary	Brush, Roller, Spray

#### Surface Preparation

Surface to be painted must be clean and free of dirt, grease, flaking paint and mildew. Dull glossy areas by sanding. Apply one or two coats of CS 415 EASY WASH after priming the surface as outlined below.

**New Plaster, Gypsum Board:** Prime with a full coat of CS 192 WALL PLUS Waterborne Micronized Stabilizing Eco Primer or CS 570 THE PERFECT PRIMER Alkyd Multi-primer & sealer.

**Masonry, Concrete, Bricks:** Prime with CS 182 WALL PLUS Solventborne, Waterproofing Stabilizing Primer or CS 181 WALL PLUS Waterborne, Alkali-resistant Primer.

**Previously Painted Surfaces:** If surface is sound, prime with CS 181 WALL PLUS Waterborne, Alkali-resistant Primer. Fill nail holes and cracks and sand when dry. Spot prime patched surfaces with CS 023 THE PERFECT PRIMER, All-purpose eco primer. If previous is old porous lime, apply and overall coat of CS 182 WALL PLUS Solventborne, Waterproofing Stabilizing Primer.

**New Wood:** Prime surfaces with CS 570 THE PERFECT PRIMER Alkyd Multi-primer & sealer or CS 023 THE PERFECT PRIMER, All-purpose eco primer.

#### Application

Stir thoroughly before and during use. Apply by brush, roller or spray. Use a short nap roller on smooth surfaces. Thin as 5% with clean water, only if necessary. Do not apply at temperatures below 10°C. Drying times are longer in cool/moist conditions.

#### Clean Up:

Clean equipment in warm, soapy water after painting. Do not empty into drains or watercourses. Dispose of empty container responsibly and according to local legislation

#### Precautions Health, Safety and Environmental Protection

•If medical advice is needed, have product container or label at hand. •Keep out of reach of children. •Keep container tightly closed. •Do not get in eyes, on skin, or on clothing. •Avoid release to the environment. •Call a POISON CENTER or a doctor if you feel unwell. •Dispose of contents and container to appropriate waste site or recycled in accordance with local and national regulation. •Safety data sheet available on request. •Contains: mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (3:1), 1,2-Benzisothiazol-3 (2H) -one, 2-OCTYL-2H-ISOTHIAZOL-3-ONE, 3-Iodo-2-propynyl N-butylcarbamate. May produce an allergic reaction. •Contains a biocidal product with fungicidal & algicidal properties. Active ingredients: butylcarbamate-3-iodo-2-propynyl (55406-53-6), 2-octyl-2H-isothiazol-3-one (26530-20-1) and zinc pyrithione (13463-41-7) to protect the coating (film). Do not empty into drains. The residual water from cleaning of the working equipment must not get into the ground or into surface waters.

POISON CENTER TEL.: +302107793777

#### Packaging and Storage

**Sizes :** 1litre, 3litres, 10 litres

**Flash Point:** none

**Storage:** not hazardous, no special requirements

