

THE PERFECT PRIMER

All-purpose eco primer

Waterborne 100% Acrylic

CS 023 00

A high quality ecological, 100% acrylic primer formulated to adhere to a wide range of interior and exterior substrates. Use on walls, wood, plaster, concrete, bricks, gypsum board, ceramic tile, formica, non-ferrous metal, glass and rigid PVC. Applies easily with minimal roller spatter and odor. Dries quickly, CS 023 The Perfect Primer, all-purpose eco primer provides outstanding adhesion and sealing. It can be used under acrylic or enamel paints as well as over new and previously painted surfaces. Eco certified according to the new criteria of the European Union Eco-labeling Board(EUEB). For more information as to why this product has been awarded the Flower visit the web-site: www.ecolabel.eu.



Performance Features:


- Excellent Adhesion
- Ideal for new wood, new galvanized Metal, glass, pvc and other hard surfaces
- Spatter Resistant
- Quick dry and recoat

Colors: Available in White and Deep Color Base.

04 Deep Base Primer: Is used where the symbol Δ is indicated. When tinted will provide a hiding base coat suitable for use under deep and intense colors.

Toxicity: Formulated without lead or mercury

Gloss Level: 0-5 at 60 degree viewing angle.



Performance Guide:

Weather Resistance

Excellent resistance to weathering.

Environmental Resistance

Excellent resistance to weather when topcoated with Colorstyle 100% acrylic finishes.

Heat Resistance

Up to 65° C.

Water Resistance

Excellent resistance to rain and condensation.



VOC (Volatile Organic Compounds): CS 023 The Perfect Primer, All-purpose Eco Primer: belongs to the category A/g WB (Primers). EU Limit: 15g/l (2010). This product contains maximum 2g/l VOC.

Spreading Rate	Volume Solids	Wet Film Thickness	Dry Film Thickness
7-8m²/L depending on surface texture and porosity.	32%	100 micrometres	32 micrometres
Dry Time at 20°C	Flexibility	Thinning	For Application By
1 hour to touch 3 hours to recoat	Passes 6 mm mandrel	5%	Brush, Roller, Spray

Surface Preparation

Surface to be painted must be thoroughly clean, dry and free of dust, dirt, grease, loose material, flaking paint, concrete salts and mildew. Remove loose material by scraping and sanding. Note: If mildew is present, remove with a commercial mildew wash, following manufacture's directions and cautions. Apply one coat. Fill nail holes, cracks and areas needing repair, then spot prime these areas.

New Wood: Spot prime all caulked nailholes and patches with CS 023 The Perfect Primer, all-purpose eco primer. Allow to dry, then apply a full coat CS 023 The Perfect Primer, all-purpose eco primer. Sand to a smooth surface.

New Gypsum Board: CS 023 The Perfect Primer, all-purpose eco primer will not raise the nap of the paper.

New Walls, Plaster and Concrete: Apply once these surfaces are dry and cured.

Brick, Masonry: Ensure loose and crumbling material is removed before priming.

Previously Painted Surfaces: Ensure surface is clean and sound.

Galvanized Metal, Stainless Steel and Aluminium: Degrease with white spirits or suitable solvent or other properly methods. Apply 1 coat CS 023 THE PERFECT PRIMER all-purpose eco primer

Glass, Rigid PVC, Ceramic Tile and other hard non-porous surfaces: Clean thoroughly with detergent and water. Apply 1 coat CS 023 THE PERFECT PRIMER all-purpose eco primer

Application

Stir thoroughly before use. Apply by roller, brush, or spray. Thin up to 5% with clean water. Do not apply when air and surface temperatures are below 10°C. Close container when not in use.

Drying: Dries in 1 hour. Can be recoated after 3 hours. Drying times are longer in cool/moist conditions.

Clean Up

Waste Management:

Remove as much as possible from brushes and rollers before cleaning. Clean brushes and equipment with water and detergent solution immediately after use. Do not empty into drains or watercourses. Dispose of empty container responsibly and according to local legislation.

Precautions Health, Safety and Environmental Protection:

If medical advice is needed, have product container or label at hand. •Keep out of reach of children •Do not get in eyes, on skin, or on clothing •Avoid release to the environment •Dispose of contents and container to appropriate waste site or recycled in accordance with local and national regulation •Keep container tightly closed. •Contains 1,2-benzisothiazol-3(2H)-one and reaction mass of 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (3:1). •May produce an allergic reaction. •Call a POISON CENTER, doctor if you feel unwell. •Safety data sheet available on request.

TEL. POISON CENTER GR: 210 7793777

Packing and Storage:

Sizes : 1 litre, 3 litre

Flash Point: none

Storage: not hazardous, no special requirements

