

## CS 895 CONCEPTS PROFESSIONAL Acrylic Stabilizing Primer Interior/Exterior use

Acrylic semi – transparent tinted slightly grey primer for emulsion and façade paints. Recommended for interior and exterior surfaces such as smooth plaster, concrete, stucco etc. Features high penetration, strong adhesion and excellent alkali resistance. Stabilizes and binds thin, porous and powdery films. Improves hiding and appearance of finish coat. Very good spreading rate. Thinning: 300-400% with water.




### Performance Features

- High penetration, strong adhesion
- Excellent alkali resistance
- Stabilizes and binds thin, porous and powdery films
- Improves hiding and appearance of finish coats
- Easy application, good spreading rate.

**Colors :** Available in semi-transparent, tinted slightly gray.

**Toxicity:** Formulated without lead or mercury

**Gloss Level:** Mat.



### Performance Guide:

#### Weather Resistance

Excellent resistance to weathering.

#### Environmental Resistance

Excellent resistance to weather when topcoated with VICTORY 2002 Acrylic Paint.

#### Heat Resistance

Up to 65° C.

#### Water Resistance

Excellent resistance to rain and condensation.



**VOC (Volatile Organic Compounds):** EU limit value for this product category A/g type WB: Primers, 30g/l (2010). This product contains max 5g/l VOC.

Spreading Rate	Volume Solids	Wet Film Thickness	Dry Film Thickness
18 - 20m <sup>2</sup> /L depending on thinning, surface preparation texture and porosity.	15%	69 micrometres	21 micrometres
Dry Time at 20°C	Flexibility	Thinning	For Application By
1 hour to touch 2 - 4 hours to recoat	Passes 6mm mandrel	300% - 400% water	Brush, Roller , Spray

### Surface Preparation - Application

Surface to be painted must be free of all loose material such as flaking and peeling paint, dust, concrete salts, form oils and powdering masonry. The surface must be clean with all traces of grease, oil, and dirt removed. Remove loose material by scraping and sanding. Stir paint thoroughly before and during use. Apply by roller, brush, or spray. Apply one coat of CS 895 CONCEPTS PROFESSIONAL Acrylic Stabilizing Primer. Do not apply at temperatures below 10°C. Drying times are longer under cool/moist conditions.

### Clean Up

#### Waste Management:

Remove as much as possible from brushes and rollers before cleaning. Clean brushes and equipment with water and detergent solution immediately after use. Do not empty into drains or watercourses. Dispose of empty container responsibly and according to local legislation.

### Precautions Health, Safety and Environmental Protection:

If medical advice is needed, have product container or label at hand• Keep out of reach of children• Do not get in eyes, on skin, or on clothing• Avoid release to the environment•Dispose of contents and container to appropriate waste site or recycled in accordance with local and national regulation•Keep container tightly closed. • Contains 1,2-benzisothiazol-3(2H)-one and reaction mass of 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (3:1). • May produce an allergic reaction. • Call a POISON CENTER, doctor if you feel unwell. • Safety data sheet available on request.

TEL. POISON CENTER GR: 210 7793777

### Packaging and Storage

**Sizes :** 0,75 litre, 3 litre, 9 litre

**Flash Point:** none

**Storage:** not hazardous, no special requirements

